

**SULPHURIC ACID 65%** 

Page: 1

Compilation date: 10/12/2012

**Revision date:** 23/01/2015

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: SULPHURIC ACID 65%

REACH registered number(s): 01-2119458838-20-XXXX

CAS number: 7664-93-9
EINECS number: 231-639-5
Product code: SULA65

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Beverage Processing Aids and Other Usages

### 1.3. Details of the supplier of the safety data sheet

Company name: Murphy and Son Ltd

Murphy & Son Ltd Alpine St, Old Basford

Nottingham
NG6 0HQ
United Kingdom

**Tel:** 0115 978 5494

Email: technical@murphyandson.co.uk

# 1.4. Emergency telephone number

Emergency tel: 0115 978 5494

(office hours only)

### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

# 2.2. Label elements

Label elements under CLP:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



**SULPHURIC ACID 65%** 

Page: 2

Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P321: Specific treatment (see instructions on this label).

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point.

### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### **Hazardous ingredients:**

SULPHURIC ACID - REACH registered number(s): 01-2119458838-20-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-639-5	7664-93-9	-	Skin Corr. 1A: H314	50-70%

# Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10

minutes. If unconscious, check for breathing and apply artificial respiration if necessary.

If unconscious and breathing is OK, place in the recovery position. Transfer to hospital

as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and

provide oxygen if available. Transfer to hospital as soon as possible.

# 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

[cont...]

**SULPHURIC ACID 65%** 

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and

away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the

escape of liquid.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage

container for disposal by an appropriate method.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

# 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

**SULPHURIC ACID 65%** 

Page: 4

# 7.3. Specific end use(s)

Specific end use(s): Beverage Processing Aids and Other Usages

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

# Hazardous ingredients:

### **SULPHURIC ACID...100%**

### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.05 mg/m3	•		-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Odourless

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Highly soluble

Viscosity: No data available.

Boiling point/range°C: >100 Melting point/range°C: <0

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: Not applicable. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: Not applicable. Vapour pressure: No data available.

Relative density: 1.55 pH: <2

VOC g/l: Not applicable.

### 9.2. Other information

Other information: No data available.

**SULPHURIC ACID 65%** 

Page: 5

# Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

# 11.1. Information on toxicological effects

## Hazardous ingredients:

#### **SULPHURIC ACID...100%**

ORL   RAT   LD50   2140	ma/ka

## Relevant hazards for substance:

Hazard	Route	Basis	
Skin corrosion/irritation	DRM	Hazardous: calculated	
Serious eye damage/irritation	OPT	Hazardous: calculated	

# Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

**SULPHURIC ACID 65%** 

Page: 6

# Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

# 14.1. UN number

UN number: UN1830

14.2. UN proper shipping name

Shipping name: SULPHURIC ACID with more than 51% acid

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

**Special precautions:** No special precautions.

SULPHURIC ACID 65%

Page: 7

Tunnel code: E
Transport category: 2

# Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

**Legend to abbreviations:** PNEC = predicted no effect concentration

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

LDLO = lethal dose low

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

OPT = optical

SULPHURIC ACID 65%

Page: 8

INH = inhalation

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.