**FININGS**

SUPER FX

TECHNICAL DATA SHEET

Description

SUPER FX is a blended formulation that has been specifically designed for the rapid sedimentation of yeast, protein and other haze forming particles, resulting in bright, clear beer.

Benefits

- Helps achieve excellent beer clarity
- Vegan friendly product
- Rapid action finings to be used in maturation, conditioning tank and cask.
- Low dosage rates, concentrated formulation
- Super FX is stable at ambient temperatures with a long shelf life
- Suitable for breweries worldwide

PRODUCT CODE

MS_SFX

COMMODITY CODE

38249996

PACKAGING (kg)

5, 25, 200 & 1225 kg

STORAGE

Keep in original container.
Keep containers sealed when not in use.

Temperature

Recommended storage temperature is 4°C - 30°C.

Do not allow the product to freeze.

Location

Store in a cool, dry place away from direct sunlight.

SHELF LIFE

At the recommended storage conditions, 12 months from date of manufacture.

Application and Rates of Use

Super FX can be added direct to DPV or during transfer of beer from fermentation vessel (FV) to conditioning tank. It can also be added directly to cask.

Rates of use:

Super FX is best added when the beer is finished fermenting and has already been cold crashed—either added during transfer or direct to tank. Action of this fining is quite rapid with excellent results achievable within 48 hours. Best results achieved at 5°C.

Rates of addition are typically within the range of 70mL - 200mL of beer. The exact rate will depend upon whether or not kettle finings have been used in the brewhouse, the addition of auxiliary finings, the degree of yeast flocculation, yeast count, pH, temperature and the residence time on chill at the end of fermentation and the strength of the beer. Optimisations should be carried out to determine the dosage rates more accurately.

Guidance For Use


- Check that the product is within its shelf life before use
- Read the Safety Data Sheet prior to use

TECHNICAL SUPPORT

+44 (0) 115 978 5494 | techsupport@murphyandson.co.uk

REGULATORY COMPLIANCE INFORMATION

Refer to the 'Product Specification Sheet' or contact us on:
+44 (0) 115 978 5494 | compliance@murphyandson.co.uk

 EST. 1887 MURPHY & SON	Product name : SUPER FX
	Product code: MS_SFX
	Doc Ref: TDS077
	Issue Date: 03/03/25
	Issue Number: V01
	Written by: Celina Dugulin
For Health & Safety Information refer to the Safety Data Sheet.	Authorised by: Iain Kenny